Custom Made Rugged Shelters



Standard, Proven and Ruggedized for Your Transportable Shelter Needs



About Product

The S-250AV shelter provides optimum performance under the most demanding field conditions. Lightweight, high strength, insulated and all weather, this shelter satisfies general-purpose applications for housing, communications and other transportable electronic equipment.

Rugged inside and outside, the S-250AV is equipped to withstand adverse weather and terrain, in addition to a high level of interior traffic. The S-280C/G shelter is constructed of foam and beam sandwich panels, which consist of a polyurethane foam core, the skins and a framework of high strength steel sheets and sections. Structural strength is assured by orientation of the floor and roof beams in transverse direction. Foam and beam panel construction provides high strength to weight ratios and facilitates ease of modification, repair, and maintenance. Shelter corners are reinforced to accept leveling jacks and to withstand side load imposed by high wind velocities.

Standard Features

Dimensions:

External: Length 20'

Width 8' Height 8'

Weight: 2500 to 3000 kg **Payload:** 4000 to 5000 kg

Lifting Eyes: Four (4) Eyes with 3" inside Clearance. **Roof Access steps:** Six (6) recessed folding steps in side wall with one handle & fixed ladder at rear wall

Air-condition: As per customer requirement.

RFI Shielding: (Optional)

Colour: PU/Epoxy (Federal Standard 595B Colour)

Please Contact us for more details









12/A Sector 26 Korangi Industrial Area Karachi 74900 Pakistan

Contact: (+92) 021-35070061 – 63, 0300 9247888 www.axpertvision.com info@axpertvision.com

